(19) World Intellectual Property Organization

International Bureau



. | 1200 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1700 | 1

(43) International Publication Date 23 June 2005 (23.06.2005)

PCT

(10) International Publication Number WO 2005/057037 A1

(51) International Patent Classification7:

F16D 3/52

(21) International Application Number:

PCT/CA2004/002094

(22) International Filing Date: 9 December 2004 (09.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/528,225

9 December 2003 (09.12.2003) US

- (71) Applicant (for all designated States except US): LITENS AUTOMOTIVE PARTNERSHIP [CA/CA]; 730 Rowntree Dairy Road, Woodbridge, Ontario LAL 5T9 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JANSEN, Christian [CA/CA]; 704-4340 Bloor St. West, Etobicoke, Ontario M9C 2A6 (CA). ANTCHAK, John [CA/CA]; 2015 Grand Vista Court, Innisfil, Ontario L9S 4A6 (CA).
- (74) Agents: IMAI, Jeffrey, T. et al.; Magna International Inc., 337 Magna Drive, Aurora, Ontario L4G 7K1 (US).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SPRING TRAVEL LIMITOR FOR OVERRUNNING DECOUPLER



(57) Abstract: A decoupler assembly for transferring rotary movement between an engine driven shaft and a serpentine belt. The decoupler includes a hub configured to be assembled to the shaft. The hub has a helical first slot formed therein. A pulley is rotatably coupled to the hub. A carrier is mounted on the hub and includes a helical second slot formed therein, as well as an anti-ramp up boss formed thereon. A thrust plate is fixed to the hub and has a slot formed therein. A torsion spring is compressed between a hub end retained in the helical first slot and a carrier end retained in the helical second slot for transferring torque between the hub and carrier. The anti-ramp up boss travels within the slot formed in the thrust plate for limiting rotation between the carrier and thrust plate and preventing rotation of the torsion spring relative to the hub and carrier.